

Table 2. Compositied assay results for phase 1 drilling of the Offset Zone and Cowboy Zone, LDI											
Drill Hole	Section	Zone	From (m)	To (m)	Length (m)	Pd g/t	Pt g/t	Au g/t	Cu%	Ni%	Co%
09-101	504N	Offset	312	328	16	2.89	0.35	0.22	0.071	0.082	0.006
09-102	504N	Offset	270	276	6	5.57	0.32	0.25	0.040	0.062	0.005
09-102	504N	Offset	327	336	9	3.24	0.38	0.29	0.101	0.101	0.007
09-102	504N	Offset	365	373	8	3.02	0.27	0.07	0.018	0.059	0.005
09-103	504N	Offset	292	299	7	4.16	0.26	0.34	0.059	0.076	0.007
09-103	504N	Offset	302	307	5	4.53	0.31	0.14	0.071	0.109	0.012
09-103	504N	Offset	355	361	6	2.38	0.26	0.12	0.043	0.080	0.006
09-104	504N	Offset	382	387	5	3.39	0.42	0.38	0.135	0.127	0.009
09-104	504N	Offset	394	399	5	2.98	0.25	0.10	0.025	0.059	0.005
09-104	504N	Cowboy	482	485	3	2.92	0.27	0.32	0.105	0.091	0.007
09-105	503N	Offset	310	321	11	2.18	0.27	0.17	0.069	0.070	0.006
09-106	503N	Cowboy	398	401	3	2.20	0.28	0.19	0.093	0.083	0.006
09-106	503N	Cowboy	464	467	3	4.24	0.36	0.45	0.133	0.158	0.010
09-107	503N	Offset	331	342	11	3.48	0.25	0.18	0.047	0.067	0.005
09-107	503N	Offset	347	363	16	5.28	0.39	0.38	0.132	0.148	0.007
09-107	503N	Offset	373	378	5	4.85	0.55	0.44	0.113	0.110	0.007
09-107	503N	Cowboy	415	419	4	2.67	0.28	0.04	0.019	0.075	0.005
09-108	503N	Offset	335	341	6	3.97	0.31	0.36	0.102	0.066	0.008
09-108	503N	Offset	382	395	13	5.01	0.55	0.45	0.137	0.163	0.008
including	503N	Offset	385	390	5	7.03	0.76	0.68	0.198	0.223	0.010
09-108	503N	Offset	406	413	7	3.11	0.41	0.30	0.098	0.113	0.006
09-109	503N	Offset	395	410	15	5.30	0.57	0.42	0.128	0.175	0.009
including	503N	Offset	399	405	6	7.48	0.79	0.54	0.159	0.227	0.010

Drill Hole	Section	Zone	From (m)	To (m)	Length (m)	Pd g/t	Pt g/t	Au g/t	Cu%	Ni%	Co%
09-110	503N	Offset	423	434	11	6.03	0.42	0.12	0.027	0.069	0.006
09-110	503N	Offset	438	444	6	3.49	0.33	0.17	0.067	0.092	0.005
09-110	503N	Cowboy	476	481	5	2.20	0.23	0.23	0.037	0.074	0.005
09-111	503N	Offset	418	423	5	3.41	0.33	0.21	0.070	0.097	0.008
09-111	503N	Offset	429	441	12	3.75	0.31	0.17	0.067	0.097	0.006
09-111	503N	Cowboy	466	475	9	2.69	0.26	0.04	0.009	0.054	0.005
09-112	503N	Offset	435	441	6	6.31	0.46	0.25	0.079	0.119	0.006
09-112	503N	Offset	451	457	6	5.91	0.34	0.10	0.019	0.069	0.005
09-112	503N	Cowboy	500	505	5	2.34	0.22	0.18	0.039	0.061	0.005
09-113	502N	Offset	248	256	8	5.05	0.63	0.56	0.142	0.170	0.009
09-113	502N	Offset	387	393	6	2.81	0.36	0.30	0.114	0.112	0.009
09-113	502N	Cowboy	437	444	7	3.69	0.38	0.18	0.120	0.119	0.006
09-114	502N	Offset	279	289	10	3.73	0.50	0.19	0.108	0.137	0.005
09-114	502N	Offset	356	362	6	3.98	0.56	0.52	0.242	0.214	0.011
09-114	502N	Offset	385	390	5	5.60	0.85	0.67	0.433	0.366	0.015
09-114	502N	Cowboy	409	415	6	2.42	0.32	0.31	0.164	0.099	0.006
09-114	502N	Cowboy	435	439	4	3.28	0.42	0.21	0.145	0.116	0.008
09-114	502N	Cowboy	529	534	5	2.25	0.22	0.16	0.078	0.070	0.006
09-115	502N	Offset	371	386	15	2.93	0.40	0.30	0.098	0.108	0.008
09-115	502N	Cowboy	431	436	5	2.53	0.31	0.20	0.077	0.088	0.006
09-116	502N	Offset	374	381	7	2.84	0.33	0.14	0.039	0.077	0.005
09-116	502N	Cowboy	435	440	5	2.24	0.26	0.19	0.077	0.091	0.005
09-117	502N	Offset	391	408	17	6.13	0.61	0.47	0.127	0.171	0.008
09-117	502N	Cowboy	475	480	5	2.29	0.26	0.09	0.056	0.082	0.005
09-118	502N	Offset	380	402	22	9.15	0.51	0.30	0.120	0.110	0.007
09-118	502N	Cowboy	486	492	6	2.17	0.30	0.08	0.033	0.071	0.005
09-119	502N	Offset	441	446	5	4.05	0.31	0.09	0.028	0.074	0.005

Drill Hole	Section	Zone	From (m)	To (m)	Length (m)	Pd g/t	Pt g/t	Au g/t	Cu%	Ni%	Co%	
09-119	502N	Offset	460	465	5	4.44	0.37	0.11	0.043	0.073	0.005	
09-119	502N	Cowboy	504	519	15	2.00	0.30	0.16	0.051	0.084	0.005	
09-120	502N	Offset	460	465	5	16.90	0.79	0.62	0.035	0.095	0.006	
09-120	502N	Cowboy	495	500	5	3.94	0.37	0.28	0.143	0.104	0.007	
09-201	501N	Offset	362	369	7	7.06	0.55	0.46	0.134	0.136	0.010	
09-202	501N	Cowboy	458	479	21	3.51	0.47	0.38	0.188	0.165	0.009	
including	501N	Cowboy	471	478	7	5.59	0.78	0.66	0.357	0.288	0.013	
09-203	501N	Offset	399	408	9	3.22	0.45	0.35	0.149	0.116	0.010	
09-204	501N	Offset	414	421	7	3.37	0.35	0.21	0.101	0.102	0.008	
09-205	501N	Offset	464	473	9	4.37	0.45	0.23	0.094	0.141	0.007	
09-206	501N	Offset	428	517	89	3.29	0.33	0.19	0.060	0.085	0.005	
including	501N	Offset	469	487	18	4.39	0.40	0.19	0.056	0.091	0.006	
including	501N	Offset	502	513	11	4.50	0.55	0.15	0.096	0.106	0.005	
09-207	501N	Offset	466	474	8	4.42	0.42	0.23	0.069	0.097	0.006	
09-207	501N	Offset	477	487	10	4.43	0.47	0.27	0.140	0.123	0.007	
09-208	500N	Cowboy	415	419	4	2.44	0.28	0.29	0.070	0.078	0.006	
09-210	500N	Offset	404	410	6	3.09	0.41	0.32	0.125	0.119	0.009	
09-210	500N	Cowboy	456	463	7	3.40	0.49	0.40	0.207	0.187	0.011	
09-210	500N	Cowboy	506	510	4	4.21	0.49	0.54	0.180	0.168	0.010	
09-211	500N	Offset	492	498	6	3.55	0.38	0.09	0.065	0.081	0.006	
09-211	500N	Offset	513	524	11	4.03	0.43	0.27	0.165	0.173	0.008	
09-211	500N	Cowboy	578	582	4	3.00	0.30	0.16	0.121	0.117	0.008	
09-212	500N	Offset	420	426	6	3.06	0.37	0.24	0.089	0.118	0.006	
09-212	500N	Offset	436	444	8	3.07	0.35	0.14	0.031	0.066	0.005	
09-212	500N	Cowboy	575	581	6	1.97	0.23	0.08	0.059	0.081	0.005	

Drill Hole	Section	Zone	From (m)	To (m)	Length (m)	Pd g/t	Pt g/t	Au g/t	Cu%	Ni%	Co%
09-213	499N	Offset	313	320	7	3.97	0.44	0.31	0.146	0.159	0.008
09-213	499N	Offset	326	340	14	3.30	0.33	0.32	0.103	0.139	0.008
09-213	499N	Cowboy	438	449	11	4.45	0.51	0.45	0.151	0.111	0.008
09-214	499N	Offset	396	404	8	3.77	0.55	0.21	0.139	0.143	0.011
09-214	499N	Cowboy	426	434	8	4.04	0.56	0.35	0.135	0.114	0.009
09-215	499N	Offset	410	417	7	2.62	0.31	0.27	0.079	0.107	0.008
09-215	499N	Cowboy	470	477	7	3.05	0.35	0.32	0.076	0.094	0.008
09-215	499N	Cowboy	479	486	7	2.95	0.37	0.16	0.047	0.075	0.005
09-216	499N	Offset	435	440	5	3.26	0.40	0.39	0.082	0.083	0.010
09-216	499N	Cowboy	461	469	8	2.61	0.33	0.27	0.105	0.104	0.006
09-216	499N	Cowboy	500	505	5	1.76	0.20	0.14	0.046	0.047	0.004
09-217	499N	Offset	430	437	7	3.23	0.39	0.20	0.059	0.089	0.005
09-217	499N	Offset	448	457	9	2.68	0.33	0.18	0.070	0.081	0.005
Notes:											
True widths are estimated to be 70-80% of hole lengths											